

Mobile tank systems for petrol

CEMO KS MOBIL EASY 120 and 190 L PG 4

ADR CERTIFIED

| Capacity / Description | Dimensions cm (l x w x h) | Weight approx. kg | Order no. |
|---|---------------------------|-------------------|-----------|
| 120L with hand pump | 80 x 60 x 45 | 23 | 10091 |
| 120L with pump 12V, 25 L/min, ATEX and automatic nozzle | 80 x 60 x 45 | 33 | 11498 |
| 120L with hand pump and hinged lid | 80 x 60 x 47 | 26 | 10092 |
| 120L with pump 12V, 25 L/min, ATEX, automatic nozzle and hinged lid | 80 x 60 x 47 | 36 | 11499 |
| 190L with hand pump | 80 x 60 x 59 | 25 | 10093 |
| 190L with pump 12V, 25 L/min, ATEX and automatic nozzle | 80 x 60 x 59 | 35 | 11500 |
| 190L with hand pump and hinged lid | 80 x 60 x 61 | 28 | 10094 |
| 190L with pump 12V, 25 L/min, ATEX, automatic nozzle and hinged lid | 80 x 60 x 61 | 38 | 11501 |
| 190L with pump 230V, 40 L/min, ATEX and automatic nozzle | 80 x 60 x 59 | 35 | 10458 |

CEMO KS-MOBIL EASY 330 L PG 4

Petrol and petrol mixtures

Basic and Premium versions certified for transport under ADR D/BAM 15862/31H2

Examinations every 2½ years corresponding ADR 6.5.4.4.1b*** and ADR 6.5.4.4.2b.

- compact design, easy to use
- all components at optimum working height
- container made of electrically conductive, highly cross-linked polyethylene
- lockable lid with steel support stays
- flashback arrestor
- contents gauge
- integral dispensing nozzle holder
- integral filler neck
- filler cap with vent and breather valves
- integral baffle
- integral forklift pockets
- integral handles
- integral recesses for ratchet straps during transport
- with self-priming pump, 12 V DC, 25 L/min*, with ATEX certification, automatic nozzle and 5 m cable
- fully assembled



flashback arrestor (330 L)

KS-Mobil Easy 330 L Premium with hose reel and galvanised steel base

Basic version

with 4 m dispensing hose DN 19, electrically conductive, 2 m earthing conductor with terminal clamp

Premium version

with hose reel with 10 m hose DN 19, electrically conductive, 10 m earthing conductor with terminal clamp with sturdy galvanised steel base, forkliftable from four sides



KS-Mobil Easy 330 L Basic

| Description | External dimensions in cm (l x w x h) | Weight (approx.) in kg | Order no. |
|-----------------------------|---------------------------------------|------------------------|-----------|
| KS MOBIL Easy 330 L Basic | 118 x 79 x 57 | 42 | 11502 |
| KS MOBIL Easy 330 L Premium | 144 x 80 x 67 | 84 | 11361 |

ACCESSORY

| | Order no. |
|---|-----------|
| Digital flow meter K24 A ATEX for mounting between dispensing hose and automatic nozzle | 10411 |

* Pump dispensing volume in free flow. Please note that the pump dispensing volume can fall sharply depending on the length and cross-sectional area of the hose. *** The transport certification for all plastic IBCs is limited to 5 years.