MINI Range

TWIN SEWAGE & WASTEWATER PUMPING STATION

The Mini Twin Range of package pump stations are designed to collect foul water from multiple properties or buildings which houses multiple people such as commercial offices and other medium sized commercial applications.

The Mini Twin Range has been designed to ensure an easy and trouble free installation and is manufactured in high grade HDPE. The Mini Twin Range of pump stations are delivered to site as a complete package, including all internal pipe work, 2 sewage pumps and alternating control panel and float switches.


This system also comes with guide rail and pedestal kit for easy pump access. The station is designed to pump through a 63mm pump main as the chamber's outlet terminates in a 2" male BSP thread.

The Mini Twin Range pump station allows for one or two 110mm inlet (to be drilled on site) to enable a quick and easy installation.

For detailed instructions for wiring and installation, please review the

installation manual.

65mm solid handling pumps are available upon request.



| Chamber Dimensions | | | Access Cover | |
|--------------------|----------------------------|------------------------|----------------|------------|
| Diameter | Height | Capacity | Size | Rating |
| 1000mm | 1000mm 1500mm 2000mm | 800L 1200L 1700L | 600 x 600 (mm) | Pedestrian |

| Model Ref | 6VX | 10VX | МС | |
|---------------|------------------|---------|-----------|--|
| Impeller type | Vortex | Vortex | Macerator | |
| Power Supply | 230 ~ 1ph ~ 50hz | | | |
| Rated Power | 0.37kW | 0.75kw | 1.2kW | |
| Rated Current | 1.9A | 4.0A | 9.2A | |
| Max Head | 6m | 10m | 16m | |
| Max Flow Rate | 5.5 l/s | 7.9 l/s | 1.8 l/s | |
| Cable Length | 10m | 10m | 10m | |
| Free Passage | 50mm | 50mm | Macerator | |

Additional Extras

Pipework & Fittings



High Level Alarms



Telemetry Alerts



Battery Backups



Servicing & Commissioning

