
## RL SX polyester filtering net - 50 micron washable cartridge







## APPLICATIONS

Filtration of: sand, scales, rust.

Domestic use: filtration of drinking water, protection of taps,

boilers, washing machines and other installations.

Technical use: pre-filtration for water-pumps, irrigation systems,

protection of industrial installations. Average life-span: about 24 months. Maintenance: wash every 3 months.

## **WORKING CONDITIONS**

Max working temperature \_\_\_\_\_ 45°C


## **SPECIFICATIONS**

Non-toxic materials, suitable for drinking water.

Filtering medium: polyester net. Armouring: polypropylene. End caps: polypropylene.

Flat seals: PVC.

suitable housing	cartridge model	cartridge height	mm			recommended
			Α	В	С	flow rate l/h
Mignon	RL Mignon SX 50 mcr	5″M	122	50	20	500
Cadet	RL 4 SX 50 mcr	4"	106	70	30	650
Medium	RL 5 SX 50 mcr	5"	125	70	30	800
Junior	RL 7 SX 50 mcr	7″	173	70	30	1100
Senior	RL 10 SX 50 mcr	10"	250	70	30	1600
Master	RL 20 SX 50 mcr	20"	505	70	30	3000



Cartridges with different filtration rates.

