



Noise Noise Emissions Maintenance





Enhanced Design Features

Power -

The Falcon Solar Light 203 harnesses the suns power through 3 extendable high grade solar panels that ensure maximum lighting performance and brightness.

Security

The Falcon Solar lighting tower comes complete with galvanized retractable stabilizers for added security when in operation.

Design Quality -

The Falcon Solar Light 203 has been manufactured with high grade steel and is powder coat painted to the highest standards and c/w certified high quality electrical components.

Easy Set Up -

The Falcon Solar lighting tower comes complete with automatic telescopic mast operated by a push button device conveniently located on the unit.

Our Mission

We design products that harvest clean energy, minimising the impact on the environment.

In line with the UK & European government commitments of realizing zero net carbon by 2050, we are focused on reducing carbon emissions throughout our business and supply chains by bringing the most innovative and advance products to market in line with progress to a circular economy.



Features

Falcon Solar Light 203 is a compact and powerful portable solar lighting tower. The FSL-203 features 4 LED lamps which provides a brighter and more environmentally-friendly lighting system.

The innovative solar panel and trailer design make the FSL-203 easy to transport and set up without taking up valuable space.



Superior Features



Manually extendable & adjustable Solar PV panels designed to maximise the suns rays during day light hours



4 x 100W tiltable LED lighting system with 8.5m electrically extendable most and 360° rotation head providing 2400 sq.m of lighting coverage



Intelligently designed electrical control panel display providing multiple user optimisation options

SECTORS





SPECIAL EVENTS



OIL, GAS & MINING



HARD TO REACH
AREAS



MILITARY



Model - FSL-203

Raco Cyctom



Brand	Falcon Falcon
Name	Solar Light Tower
Model	FSL-203
Material Falcon	Steel Q235

Powder Outdoor Type

Transport Dimension (LxWxH) 2250 x 2200 x 2200 (mm)

Operate Dimension (LxWxH) 3250 x 4400 x 9000 (mm)

Weight 1600kg

System Voltage DC24V

Solar System

Charging Time

Solar Panel 4 x 460W Monocrystalline Silicon 144pcs

Voltage DC39V

7 hours



Light System

LED flood light 4 x 150W outdoor waterproof 90000lm

Protection Class

Efficiency 150Lm/W

Voltage DC24V

Running Time 20.5 hours

Mast System

Body Steel 0235 Galvanized

Fastener Stainless steel 304

Wire Rope Stainless steel 316 8mm

Type Square Telescopic

Height 8.5m

Section 5

Rotation 360° automatic (optional)

Tilt 90° automatic (optional)

Spring Cable Power Supply

Lifting Method Electric lifting

Recommended Loading 5kg ~ 70kg


Windproop 117kph

Charger System

Rated Power 2.5kW / 2.5kVA


Frequency 50Hz / 60Hz

Plug & Socket 1 x AC 110V/220V Input



Transport Dimensions

Length (L) (mm)	2250	Weight (Kg)	1600kg
Width (W) (mm)	2200	Loading capacity in 40 HQ (units)	05
Height (H) (mm)	2200		



Harvesting Clean Energy / Protecting Our Environment



LEP	3 x 200Ah BMS
Voltage	DC25.6V
Power Capacity	15360W.h
Control System	
Solar Controller	Victron MPPT 70A
Efficiency	95%+
Detection & Protection	Short-Circuit, Overload, High Voltage, High Temperature
Timer	Manual
Whole Machine	Battery Isolator, Light on-off
Trailer System	
Standard	US / AU / EU
Tow Hitch	50mm / 2" Ball Type
Trailer Light	7 Pin
Jockey Wheel	200mm / 8"
Axle	Single Suspension Bump Brake
Tire Falcon	2 x 15 inch
Wheel Chock	2 Ealcon
Forklift Hole	2
Outrigger	4 x Manual Galvanized
Warranty	3 years