

Water Management Solutions

Klargester AquaOil Bypass MDPE and GRP / Full retention MDPE and GRP separator range

HVO
ready**




170 – 69,444m²
Available to cover
flow rates up to
285 litres
per second



Why choose an AquaOil fuel and oil separator?

- Total peace of mind offered through SmartServ Pro remote monitoring system, for early fault detection and in line with Kingspan's Planet Passionate programme
- Total flexibility, with deep invert options available
- Range tested against full flow
- Easily utilised as part of SuDS Management Train
- Full range of bypass and full retention separators available



Our range has been tested against full flow - why is this important?

Our units have been tested at their maximum flow rate (10l/s), unlike some products which have been tested based on bypass and therefore only 10% of the flow. This ensures total accuracy of our silt retention results, by replicating the full effect of the silt wash through.

As part of our Planet Passionate programme, Kingspan are dedicated to delivering innovative surface water management technologies, developed on the back of 70 years' experience.

*Terms and conditions apply. View online at <https://www.kingspan.com/gb/en-gb/products/wastewater-management/warranty-terms>

**Also suitable for Midel Oil



**WE ARE
PLANET
PASSIONATE**

Product Code	Flow (l/s)	Drainage Area (m²)	Silt Capacity (ltrs)	Oil Capacity (ltrs)	Length (mm)	Diameter (mm)	Manhole Cover Dimensions (mm)	Base to Inlet Invert (mm)	Base to Inlet Invert (mm)	Min. Inlet Invert (mm)	Std Pipework Diameter (mm)
Polyethylene Chamber Construction											
NSFP003	3	170	300	30	1700	1350	600	1410	1335	550	160
NSFP006	6	335	600	60	1700	1350	600	1410	1335	550	160
GRP Chamber Construction											
NSFA010	10	555	1000	100	2610	1225	600	1050	1000	500	200
NSFA015	15	835	1500	150	3910	1225	600	1050	1000	500	200
NSFA020	20	1115	2000	200	3230	2010	600	1810	1760	1000	315
NSFA030	30	1670	3000	300	3960	2010	600	1810	1760	1000	315
NSFA040	40	2225	4000	400	4750	2010	600	1810	1760	1000	315
NSFA050	50	2780	5000	500	5790	2010	600	1810	1760	1000	315
NSFA065	65	3610	6500	650	7360	2010	600	1810	1760	1000	315
NSFA080	80	4445	8000	800	5744	2820	600	2500	2450	1000	315
NSFA100	100	5560	10000	1000	6200	2820	600	2500	2450	1000	400
NSFA125	125	6945	12500	1250	7365	2820	600	2500	2450	1000	450
NSFA150	150	8335	15000	1500	8675	2820	600	2550	2450	1000	525
NSFA175	175	9725	17500	1750	9975	2820	600	2550	2450	1000	525
NSFA200	200	11110	20000	2000	11280	2820	600	2550	2450	1000	600
NSFA210	210	11667	21000	2100	11994	2820	600	2550	2450	1000	600
NSFA225	225	12500	22500	2250	12766	2820	600	2550	2450	1000	600
NSFA240	240	13333	24000	2400	13528	2820	600	2550	2450	1000	600
NSFA255	255	14167	25500	2550	14300	2820	600	2550	2450	1000	600
NSFA270	270	15000	27000	2700	15071	2820	600	2550	2450	1000	600
NSFA285	285	15833	28500	2850	15833	2820	600	2550	2450	1000	600

Forecourt Separator Range Technical Specifications

Sepaator Class	Backfill Type	Total Capacity (Ltrs)	Darinage Area (m²)	Peak Flow Rate (l/s)	Length (mm)	Diameter (mm)	Access Shaft Diameter (mm)	Base Inlet Invert (mm)	Base to Outlet Invert (mm)	Standard Fall Across (mm)
1	Concrete	10000	720	15	3915	2020	600	2180	2130	50
1	Concrete	10000	115	20	3915	2020	600	2180	2130	50

Bypass Separator Range Technical Specifications

Model Reference	Flow (l/s)	Peak Flow Rate (l/s)	Drainage Area (m²) Based on UK rainwater flow	Storage Capacity (Ltrs)		Length (mm)	Diameter (mm)	Access Shaft Diameter* (mm)	Base Inlet Invert (mm)	Base to Outlet Invert (mm)	Standard Fall Across (mm)	Min Inlet Invert (mm)	Standard Pipework Diameter (mm)**
				Silt	Oil								
Polyethylene Chamber Construction													
NSBP003	3	30	1670	300	45	1700	1350	600	1420	1320	100	500	160
NSBP004	4.5	45	2500	450	60	1700	1350	600	1420	1320	100	500	160
NSBP006	6	60	3335	600	90	1700	1350	600	1420	1320	100	500	160
GRP Chamber Construction													
NSBE010	10	100	5560	1000	150	2069	1220	750	1450	1350	100	700	315
NSBE015	15	150	8335	1500	225	2947	1220	750	1450	1350	100	700	315
NSBE020	20	200	11111	2000	300	3893	1220	750	1450	1350	100	700	375
NSBE025	25	250	13890	2500	375	3575	1420	750	1680	1580	100	700	375
NSBE030	30	300	16670	3000	450	4265	1420	750	1680	1580	100	700	450
NSBE040	40	400	22222	4000	600	3230	1920	600	2185	2035	150	1000	500
NSBE050	50	500	27778	5000	750	3960	1920	600	2185	2035	150	1000	600
NSBE075	75	750	41667	7500	1125	5941	1920	600	2235	2035	200	950	675
NSBE100	100	1000	55556	10000	1500	7661	1920	600	2235	2035	200	950	750
NSBE125	125	1250	69444	12500	1875	9548	1920	600	2235	2035	200	950	750

*Some units have more than one access shaft - diameter of largest shown | **Large pipework available on request.

For more information on any of our products: T: +44 (0)28 3026 6799

E: klargestinfo@kingspan.com or visit klargest.ie

We take every care to ensure that the information in this document is accurate at the point of publication. Specification may vary (within a small parameter) due to manufacturing process variations or environmental conditions. All images are for illustration purposes only and should not be taken as binding. The actual product may vary, and specification/dimensions/colour/other attributes may differ. To ensure you are viewing the most recent and accurate product information, please scan the QR code to the right. ©Kingspan and the Lion Device are Registered Trademarks of the Kingspan Group plc in the UK, Ireland and other countries. All rights reserved. Registered in Country No.NI017631. Registered Office: 180 Gilford Road, Portadown, Co. Armagh, BT63 5LF. VAT GB412 5124 03

04/2025_v2_4360.01.ie

