

Description	Value
General information:	
Product name:	Unilift AP50B.50.08.1.V
Product No:	96004587
EAN number:	5700391489549
	5700391489549
Technical:	
Max flow:	6.67 l/s
Head max:	11 m
Type of impeller:	VORTEX
Maximum particle size:	50 mm
Materials:	
Pump housing:	Stainless steel
	DIN W.-Nr. 1.4301
	AISI 304
Impeller:	Stainless steel
	DIN W.-Nr. 1.4301
	AISI 304
Installation:	
Pump outlet:	R 2"
Maximum installation depth:	7 m
Inst dry/wet:	S
Installation:	horizontal or vertical
Auto-coupling:	Y
Liquid:	
Pumped liquid:	Any Newtonian liquid
Maximum liquid temperature:	40 °C
Density at selected liquid temperature:	998.2 kg/m ³
Electrical data:	
Type of motor:	PSC
Power input - P1:	1.2 kW
P2:	0.74 kW
Mains frequency:	50 Hz
Rated voltage:	1 x 230 V
Rated current:	5.37 A
Cos phi - power factor:	0.97
Rated speed:	2790 rpm
Capacitor size - run:	16 µF/400 V
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Motor protec:	CONTACT
Thermal protec:	internal
Length of cable:	10 m
Type of cable plug:	SCHUKO
Others:	
Net weight:	11.5 kg
Gross weight:	12.5 kg
Danish VVS No.:	391272112
Swedish RSK No.:	5885937
Country of origin:	GB
Custom tariff no.:	84137021

