



TITLE  
**PW160.INS.AG**

DRAWN BY  
**C.MORRIS**

DATE  
**05/12/2017**

CUSTOMER  
**CUSTOMER**

**NOTE:**  
All Purewater tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.

ALL DIMENSIONS +/- 5mm  
UNLESS OTHERWISE STATED

DESCRIPTION:  
**PW160 One piece cold water storage tank suitable for AG/AF Air gap**

**A4**

ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
08/09/2017	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	760 x 460 x 460mm
EXTERNAL DIMENSIONS	950 x 655 x 499mm
NOM. CAPACITY	160 Litres
DRY WEIGHT	13 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	131006
MATERIAL	GRP

**purewater** storage ltd

SCALE:1:10

SHEET 1 OF 1