950 LITRE U.N. APPROVITANKS.ie

OUTER BUND TANK: Corrosion free, Robust Heavy Duty Polyethylene outer bund tank.

INNER TANK: Corrosion free, Robust Heavy Duty Polyethylene inner tank to prevent fuel contamination. Moulded in trigger nozzle storage. 2" filler cap. Contents gauge. Pressure relief valve. 1" manual vent valve fitted. Fittings to run two generators simultaneously with the lid locked. The inner tank is also approved for 10 years

FRAME: Galvanised 5mm steel frame. c/w built in fork sockets on all sides. Four corner lifting eyes. Gas strut assisted secure lockable steel access lid.

STORAGE: Approved to stack 2 high when full and 3 high when empty.

OPTIONAL PUMPS: 12V Pump or Single diaphragm hand pump Either pump comes complete with suction pipe c/w ball valve, in line 'Y' strainer,15' length of 1" diesel hose and c/w trigger nozzle.



FINISH: Black Polyethylene outer tank as standard. Other colours available. Galvanised frame and lid.

BRIMFUL CAPACITY: 985 Litre

DIMENSIONS: (Approximate)

Width: 1213mm Length: 1213mm

Height: 1410mm overall Laden weight: 1100kg Unladen weight: 290kg

