

2000 LITRE U.N. APPROVED BUNDED DIESEL

POLYCUBE

OUTER BUND TANK:

Corrosion free, robust/heavy duty Polyethylene.

INNER TANK: Corrosion free, robust/heavy duty Polyethylene inner tank to prevent fuel contamination. Moulded in trigger nozzle storage. 2" filler cap.

Contents gauge. Pressure relief valve. 1" manual vent valve fitted. Fittings to run two generators simultaneously with the lids locked, as standard (option to run four generators). The inner tank is also approved for 10 years.

FRAME: Galvanised 5mm reinforced robust steel frame with 5mm protective bottom base plate c/w built in fork sockets on two sides. Four corner lifting eyes. Two Gas strut assisted secure lockable steel access lids.

STORAGE: Approved to stack 2 high when full and 3 high when empty.

OPTIONAL PUMPS: 12V Pump or Single diaphragm hand pump, either pump comes complete with suction pipe c/w ball valve, in line 'Y' strainer, 15' length of 1" diesel hose and trigger nozzle. Two pumps can be fitted to be used at the same time.

FINISH: Black Polyethylene outer tank as standard. Other colours available. Galvanised frame and lid.

DIMENSIONS: (Approximate)

Width: 1213mm
Length: 2500mm
Height: 1430mm
Laden Weight: 2300kg
Unladen Weight: 580kg

