

2000 LITRE WATER EU HIGHWAY BOWSER



CHASSIS: Constructed from 5mm pressed steel section fully welded with a front standing plate and 100 x 50 RSC 'A' frame drawbar.

AXLE/SUSPENSION: Single Knott-Avonride 3000kg torsion beam axle fitted with 300 x 60 auto reverse brakes.

WHEELS AND TYRES: 2 no. 235 /85 x 16 x 12 ply radial tyres on 5 stud 61/2" pcd rims.

COUPLING: Knott-Avonride 3000kg capacity posibrake over run auto reverse coupling c/w breakaway cable, spring assisted handbrake lever, fitted with 40mm eye or 50mm ball.

TANK: Polyethylene moulded tank, elliptical in section, with internal anti surge baffle & fitted with a 22" lockable outer hinged manlid cover, inner sealed vented manlid. 2" front draw off, 2 rear outlet connections. Tank secured to chassis with 2 stainless steel straps.

ANCILLARY EQUIPMENT: moulded mudguards, mud flaps, front telescopic jockey wheel, Side reflectors, & front markers, full road lighting c/w 13 pin plug and 7 pin adapter.

PUMP: Optional on request.

FINISH: Polyethylene tank in yellow, green, red or blue drinking water only. Chassis galvanised as standard. Primer and two top coats in BS colour optional on request.

DIMENSIONS: (approximate)

Width: 1.982m (78")

Length: 3.530m (139")

Height: 1.600m (63")

Laden weight: 2800kg

Unladen weight: 515kg approx

Towing height: (level) 480mm