



TransMaster

Safe and environmentally friendly transport of diesel

- ADR double walled tank
- Waterproof transportable tank for diesel oil
- Inner baffle for safe transport
- The outer tank can contain 125% of the inner tank volume
- Sandblasted and painted to C3, 140 microns
- 2 tanks stackable when full, 3 tanks when empty
- Easy to install with pump
- Produced with or without door
- Secure lockable lid
- Upgrade for transport of gasoline possible

Technical data:

- European ADR certificate for transportation of dangerous liquids on public roads
- ADR/RID 2011 approved
- UN 1202 approved
- UN 1203 approved
- Material of container steel sheet
- Material of end caps steel sheet
- Wall thickness 3 or 4 mm
- Lacquering C3 A 3.11
- Material S235JR (St 37) - 1.0037

TransMaster with door

Model	Length	Width	Height	Weight	Volume
750	1772 mm	1160 mm	1060 mm	560 kg	750 L
1000	1772 mm	1160 mm	1310 mm	685 kg	1000 L
1500	2276 mm	1160 mm	1310 mm	885 kg	1500 L
2000	2776 mm	1160 mm	1310 mm	1010 kg	2000 L
2500	3276 mm	1160 mm	1310 mm	1140 kg	2500 L
3000	3756 mm	1160 mm	1310 mm	1275 kg	3000 L

TransMaster without door

Model	Length	Width	Height	Weight	Volume
400	1512 mm	1160 mm	710 mm	435 kg	400 L
500	1512 mm	1160 mm	810 mm	475 kg	500 L
600	1512 mm	1160 mm	910 mm	485 kg	600 L
750	1512 mm	1160 mm	1060 mm	500 kg	750 L
1000	1512 mm	1160 mm	1310 mm	535 kg	1000 L
1500	1976 mm	1160 mm	1310 mm	735 kg	1500 L
2000	2476 mm	1160 mm	1310 mm	860 kg	2000 L
2500	2976 mm	1160 mm	1310 mm	990 kg	2500 L
3000	3472 mm	1160 mm	1310 mm	1125 kg	3000 L

Equipment - Standard

- Equipment varies according to country

- 2 pcs. of 1" suction pipe
- Level indicator
- 2" filling cap
- Whistle with 1" ball valve
- Safety/Ventilation valve
- Lock bracket
- Manhole 570 x 407 mm
- Forklift pockets
- Galvanised lifting corners

Equipment - Optional

- 12, 24 or 230 volt pump
- Meter
- Filter
- Hose
- Automatic nozzle
- Nozzle holde
- Chains for lifting
- Quick coupling
- Overfill protection
- Lock
- Lifting arm (Volvo)